

| | | |
|---|--|-----------------------|
| | | |
| LANOVA TRADE (HE BEI) CO.,LTD. | | |
| ADD: ROOM 1516, BLOCK B, CENTURY CENTRE BUILDING, NO 363, TIYU SOUTH STREET, | | |
| SHIJIAZHUANG, HEBEI, CHINA | | |
| TECHNICAL DATA SHEET | | |
| | | DATE: JUL 8, 2025 |
| GENERAL DESCRIPTION OF GOODS | | |
| PVC COATED FENCE | | |
| GALVANIZED WIRE AND THEN PVC COATED | | |
| ITEM | | |
| 100X75MMX1.6/2.0MMX0.6X10M GREEN RAL6005/ ANTHRACITE RAL7016 | | |
| | | |
| RAW MATERIAL CHEMICAL COMPOSITION | | |
| ELEMENT | | |
| C (Carbon) | ≤0.10% | |
| Mn (Manganese) | ≤0.6% | |
| Si (Silicon) | ≤ 0.3% | |
| P (Phosphorus) | ≤ 0.045% | |
| S (Sulfur) | ≤ 0.035% | |
| The chemical composition is in accordance with | | |
| EN 10 016-2(Non-alloy steel rod for drawing and/or for cold rolling) | | |
| | | |
| WIRE DIAMETER AND TOLERANCE | | |
| WIRE PROPERTIES, NORMAL WIRE DIAMETER | | |
| | GALVANIZED CORE WIRE | AFTER PVC COATED |
| WIRE | 1.60± 0.05MM | 2.00± 0.1MM |
| The wire diameter is in accordance with | | |
| EN 10218-2(Steel wire and wire products - General - Part 2: Wire dimensions and tolerances) | | |
| | | |
| MESH SIZE AND TOLERANCE | | |
| SPACING OF THE LINE WIRES: 101.60MM | | |
| SPACING OF THE CROSS WIRE : 76.20MM | | |
| | | |
| WIDTH AND LENGTH | | |
| WIDTH : 0.6M | | TOLERANCE: ± 20MM |
| LENGTH : 10M | | TOLERANCE: 0%--2% |
| | | |
| TENSILE STRENGTH AND ZINC COATING | | |
| ZINC COATING | TENSILE STRENGTH | |
| 8-10G/M2 | 350-400MPA | |
| | | |
| Date | | Authorized By WangWei |
| 2025-7-8 | 河北蓝沃贸易有限公司 LANOVA TRADE (HEBEI) CO.,LTD | |

周 健